



# SERIES: P11

**Dial:** 1½", 2", 2½", 4", 6", 8", 10"

**Accuracy:** 1%, 1.6%, 2.5%

## DESCRIPTION

Indumart *P11 Series* Standard Pressure Gauges with Steel Casing are general purpose gauges suitable for a broad range of commercial and industrial applications. These dry gauges are used where liquid or gaseous media are not highly viscous and do not attack copper alloys.

Due to their durability, Indumart *P11 Series* pressure gauges withstand difficult applications and thus are distinguished among all commercial pressure gauges available in the market.

Optionally, the *P11 Series* may be ordered with stainless steel, chrome-plated steel or brass case. Back and front flange accessories are available for wall and panel mounting.



## SPECIFICATIONS

<b>Accuracy</b>	2.5% for 1½" & 2" dials; 1.6% for 2½" & 4" dials; 1% for 6", 8" & 10" dials;
<b>Dial Sizes</b>	1½" (40 mm), 2" (50 mm), 2½" (63 mm), 4" (100 mm), 6" (160 mm), 8" (200 mm), 10" (250 mm)
<b>Case</b>	Steel black (standard) chromed steel, st. steel or brass (option)
<b>Bezel</b>	Push on ring for 1½", 2" & 2½" dials; Ring with screws for 4", 6", 8" 10" dials
<b>Connection Thread</b>	Back, bottom ½" NPT (1½" dial only), ¼" NPT (2", 2½" & 4" dials) ½" NPT (option for 4" dial) ½" NPT (6", 8" & 10" dials) BSP thread (option)
<b>Window</b>	Glass
<b>Bourdon Tube</b>	Brass
<b>Max. Temperature Range</b>	60°C 0...10 to 0...8000 psi; 0...60 to 0...60000 kPa; 0...0.6 to 0...600 bar Vacuum and compound ranges are available; see the Range Table

## ORDER CODES

**Model P11**

### CONNECTION

Back  
Bottom

K  
T

### DIAL SIZE

40 mm (1½")  
50 mm (2")  
63 mm (2½")  
100 mm (4")  
160 mm (6")  
200 mm (8")  
250 mm (10")

0  
1  
2  
4  
6  
8  
9

### OPTIONS (more than one option may be selected)

Stainless Steel Internals & Socket  
Chromed Steel Case (available for 40, 50, & 63 mm dials)  
Brass Case (available for 40, 50, & 63 mm dials)  
St. Steel Case (available for 40, 50, & 63 mm dials)  
½" Process Connection (100 mm dial only)  
Push-in Plexiglas Window  
Oxygen Service  
BSP Thread  
Back Flange for wall mounting (not for 40 mm dial)  
Front Flange for flush mounting (100 mm dial only)

IT  
CH  
CB  
CT  
TH  
WP  
OX  
TB  
MK  
MF

**Example: P11T4-TB,MF**