



SERIES: P14

Dial: 1½", 2", 2½"
Accuracy: 1.6%, 2.5%

DESCRIPTION

Indumart *P14 Series* Standard Pressure Gauges with ABS Casing are low cost, general purpose gauges suitable for a broad range of commercial and industrial applications. These dry gauges are used where liquid or gaseous media are not highly viscous and do not attack copper alloys.

The *P14 Series* can also be supplied with steel or brass case, and with back flange for wall mounting.



SPECIFICATIONS

Accuracy	1.6% (2½" dial), 2.5% others
Dial Sizes	1½" (40 mm), 2" (50 mm), 2½" (63 mm)
Case	ABS plastic (standard) brass, steel & 304SS (option)
Connection	Back or bottom
Thread	⅛" NPT (1½" dial only), ¼" NPT (2" & 2½" dials); BSP thread (option)
Window	Push in, plexiglas
Bourdon Tube	Brass
Max. Temperature	60°C
Range	0...10 to 0...8000 psi; 0...60 to 0...60000 kPa; 0...0.6 to 0...600 bar Vacuum and compound ranges are available; see the Range Table

DIMENSIONS (mm) & WEIGHT			
	Ø40 mm	Ø50 mm	Ø63 mm
D1	42*	50.5	63
D2	42*	50.5	62
H1	58	70	87
H2	41	49	51
L	25	28	28
Weight (g)	60	100	140


* 40 mm with stainless steel, brass or steel cases

ORDER CODES

Model P14

CONNECTION

Back
Bottom



DIAL SIZE

40 mm (1½")
50 mm (2")
63 mm (2½")




OPTIONS (more than one option may be selected)


Stainless Steel Case
Steel Case
Brass Case (40 and 50 mm dials only)
BSP Thread
Back Flange (63 mm dial with steel case only)



Example: P14T2-CS,MK



Bottom connection



Centre back connection

Specifications may change without prior notice.